

Schedule C

Weight Knockdown Formula

Adjacent Axle Groups	Observed Spacing	GVW Reduction
Single Axle-Single Axle		
(Min 3.0 m required)	2.5-2.99 m	1000 kg
	2.0-2.49 m	2000 kg
	1.5-1.99 m	3000 kg
	1.0-1.49 m	4000 kg
Single Axle-Tandem		
(Min 3.0 m required)	2.5-2.99 m	1000 kg
	2.0-2.49 m	2000 kg
	1.5-1.99 m	3000 kg
	1.0-1.49 m	4000 kg
Single-Tridem		
(Min 3.0 m required)	2.5-2.99 m	1000 kg
	2.0-2.49 m	2000 kg
	1.5-1.99 m	3000 kg
	1.0-1.49 m	4000 kg
Tandem-Tandem		
(Min 5.0 m required)	4.5-4.99 m	1000 kg
	4.0-4.49 m	2000 kg
	3.5-3.99 m	3000 kg
	3.0-3.49 m	4000 kg
	2.5-2.99 m	5000 kg
	2.0-2.49 m	6000 kg
	1.5-1.99 m	7000 kg
	1.0-1.49 m	8000 kg
Tandem-Tridem		
(Min 5.5 m required)	5.0-5.49 m	1000 kg
	4.50-4.99 m	2000 kg
	4.0-4.49 m	3000 kg
	3.5-3.99 m	4000 kg
	3.0-3.49 m	5000 kg
	2.5-2.99 m	6000 kg
	2.0-2.49 m	7000 kg
	1.5-1.99 m	8000 kg
	1.0-1.49 m	9000 kg

82/17 s1