

**Schedule C**

Weight Knockdown Formula

<b>Adjacent Axle Groups</b>	<b>Observed Spacing</b>	<b>GVW Reduction</b>
<b>Single Axle-Single Axle</b>		
(Min 3.0 m required)	2.5-2.99 m	1000 kg
	2.0-2.49 m	2000 kg
	1.5-1.99 m	3000 kg
	1.0-1.49 m	4000 kg
<b>Single Axle-Tandem</b>		
(Min 3.0 m required)	2.5-2.99 m	1000 kg
	2.0-2.49 m	2000 kg
	1.5-1.99 m	3000 kg
	1.0-1.49 m	4000 kg
<b>Single-Tridem</b>		
(Min 3.0 m required)	2.5-2.99 m	1000 kg
	2.0-2.49 m	2000 kg
	1.5-1.99 m	3000 kg
	1.0-1.49 m	4000 kg
<b>Tandem-Tandem</b>		
(Min 5.0 m required)	4.5-4.99 m	1000 kg
	4.0-4.49 m	2000 kg
	3.5-3.99 m	3000 kg
	3.0-3.49 m	4000 kg
	2.5-2.99 m	5000 kg
	2.0-2.49 m	6000 kg
	1.5-1.99 m	7000 kg
	1.0-1.49 m	8000 kg
<b>Tandem-Tridem</b>		
(Min 5.5 m required)	5.0-5.49 m	1000 kg
	4.50-4.99 m	2000 kg
	4.0-4.49 m	3000 kg
	3.5-3.99 m	4000 kg
	3.0-3.49 m	5000 kg
	2.5-2.99 m	6000 kg
	2.0-2.49 m	7000 kg
	1.5-1.99 m	8000 kg

	1.0-1.49 m	9000 kg
--	------------	---------

81/01 Sch C